



*Doppelschere  
Herkules*

TYP	NUTZLAST KG	NUTZHUB MM	LÄNGE MM	BREITE MM	BAUHÖHE MM	HUBZEIT SEK.	LEISTUNG KW
<b>SXX_005_200</b>	500	2000	1500-2000	800-1600	400	34	3,0
<b>SXX_005_200</b>	500	2000	1500-2000	800-1600	450	34	3,0
<b>SXX_005_250</b>	500	2500	2000-2500	800-1600	450	36	3,0
<b>SXX_010_165</b>	1000	1650	1300-1500	800-1300	290	34	3,0
<b>SXX_010_165</b>	1000	1650	1300-1750	800-1300	335	34	3,0
<b>SXX_010_200</b>	1000	2000	1500-2000	800-1600	400	34	3,0
<b>SXX_010_200</b>	1000	2000	1500-2000	800-1600	450	34	3,0
<b>SXX_010_250</b>	1000	2500	2000-2500	800-1600	450	36	3,0
<b>SXX_010_330</b>	1000	3300	2500-3000	1300-2900	600	51	4,0
<b>SXX_020_165</b>	2000	1650	1300-1500	800-1500	290	34	3,0
<b>SXX_020_165</b>	2000	1650	1300-1750	800-1500	335	34	3,0
<b>SXX_020_200</b>	2000	2000	1500-2000	800-2000	450	34	3,0
<b>SXX_020_250</b>	2000	2500	1500-2000	800-2000	450	45	3,0
<b>SXX_020_330</b>	2000	3300	2500-3000	1300-2900	600	51	4,0
<b>SXX_030_330</b>	3000	3300	2500-3400	1300-3300	600	60	5,5
<b>SXX_030_335</b>	3000	3350	2600-3200	2900-3300	600	60	5,5
<b>SXX_030_450</b>	3000	4500	3400-4000	1300-3300	1000	80	5,5